


Aluminium In-line Sliding and Lift & Slide Doors




In-line Sliding Doors




2 Pane

Minimum width 1400mm (at 2100mm high) Maximum width 4500mm Maximum Height 2300mm



3 Pane (Triple Track)

Minimum width 2700mm Maximum width 6000mm Maximum Height 2300mm




4 Pane

Minimum width 3600mm Maximum width 6000mm Maximum Height 2300mm


Lift and Slide Doors (Duo Rail)






2 Pane

Minimum width 1400mm (at 2100mm high) Maximum width 4500mm Maximum Height 2400mm



3 pane

Minimum width 2700mm Maximum width 6000mm Maximum Height 2400mm



4 pane

Minimum width 3600mm Maximum width 6000mm Maximum Height 2400mm

Colour Range

for fast delivery







Charge as standard RAL dual colour

Configurations Door sash width cannot be less than 3x smaller than the height of the door

Aluminium In-line Sliding and Lift & Slide Doors

Combining high performance with stunning design, our 'In-line Sliding' and 'Lift & Slide' doors provide a versatile solution for any architectural project.


'Choices' Optio BSC94 In-line Sliding and

Lift and Slide options




Optional 45mm Slim Interlock - Sliding and Lift and Slide

Standard Interlock



As overall sizes increase, additional external reinforcing will be required



Threshold and Sash

Upgrades/Options

- ✓ A range of RAL single or dual colour
- ✓ PAS 24 / Doc Q (2 pane In-line slider only)
- ✓ Brushed chrome handles
- ✓ Triple track slider no cill available 155mm frame
 - 6 week lead time
- √ 45mm slim interlock



Why not consider the other collections available from The Character brand